



Product Service

# CERTIFICATE

No. Z1A 115135 0001 Rev. 00

**Holder of Certificate:** Kern Studer AG

Weberrütistrasse 9  
8833 Samstagern  
SWITZERLAND

**Certification Mark:**



**Product:** Storage equipment and devices  
Painting deposit installations

**Tested according to:** PPP 51028C:2018  
AfPS GS 2019:01 PAK

With this certificate, in its capacity as a notified GS body, TÜV SÜD Product Service GmbH issues the GS Mark to the named certificate holder for the declared product with the named model designation in accordance with section 20 ProdSG (German Product Safety Act). The product meets the safety and health requirements of section 20 (3) ProdSG. The manufacturer is reminded of their obligations in accordance with section 24 ProdSG. The certification marks shown above can be affixed on the product. It is not permitted to alter the certification marks in any way. In addition, the certificate holder must not transfer the certificate to third parties. This certificate is valid until the listed date, unless it is cancelled earlier. All applicable requirements of the testing and certification regulations of TÜV SÜD Group have to be complied. For details see: [www.tuvsud.com/ps-cert](http://www.tuvsud.com/ps-cert)

**Test report no.:** 713227174

**Valid until:** 2027-04-05

**Date,** 2022-04-06

( Ulrich Sommer )

# CERTIFICATE

No. Z1A 115135 0001 Rev. 00

**Model(s):** **Systeme DL-100, DL-120, M-40, M-50, L-30, BL-10, BL-30, Art Gallery**

## Parameters:

<b>System DL-100</b>	Aluminium rail ceiling-running Load with 2 roller units NIKO 23.000, max. 200 kg Load with 4 roller units NIKO 23.000 (Tandem), max. 400 kg
<b>System DL-120</b>	Aluminium rail ceiling-running Load with 2 roller units NIKO 24.000, max. 400 kg Load with 4 roller units NIKO 24.000 (Tandem), max. 800 kg
<b>System M-40</b>	Steel rail ceiling-running Load with 2 roller units NIKO 24.000, max. 400 kg Load with 4 roller units NIKO 24.000 (Tandem), max. 800 kg
<b>System M-50</b>	Steel rail ceiling-running Load with 2 roller units NIKO 25.000, max. 600 kg Load with 4 roller units NIKO 25.000 (Tandem), max. 1200 kg
<b>System L-30</b>	Linear guide ceiling-running Load with 2 Linear bearing Ø 30 mm, max. 500 kg Load with 8 Linear bearing Ø 30 mm, max. 2000 kg
<b>System BL-10</b>	Floor rollers at floor-running Load with 2 rollers, max. 100 kg
<b>System BL-30</b>	Aluminium rail floor-running Load with 2 fixed rollers, max. 1000 kg Load with 4 fixed rollers, max. 2000 kg
<b>System Art Gallery</b>	Floor rollers at floor-running Load with 2 rollers, max. 100 kg
<b>Accessories</b>	Picture hook single: Ø 3 mm, max. 10 kg Picture hooks single: Ø 4 mm, max. 30 kg Picture hooks double: Ø 4 mm, max. 50 kg Label holder Anti-tilt protection Drop trays: max. 15 kg